

**DESCRIPTION**

Ventilation hoods VH-S are destined for installation in ventilation systems of special category spaces of ro-ro ships. They are provided with weather-tight/fire cover in accordance to SOLAS regulations. VH-S type hoods can be installed on weather decks. VH-S hoods consist of flanged coaming and cover actuated by pneumatic cylinder fitted on the housing of the hood. Optionally hood may be delivered with limit switches for remote indication of position of cover in ordinary or non-sparking execution (Ex-class must be specified by the buyer). Coaming is made of carbon steel St3Sx, hot-dip galvanized, wire gauze is made of stainless steel 316 and spindle of closing device – stainless steel. By ordering specify required nominal diameter DN.

**TECHNICAL SPECIFICATION & DIMENSIONS**

DN	Dimensions [mm]									Weight [kg]
	ØA	ØB	C	NxØD	E	F	ØG	H	J	
400	460	490	12	24x12	240	120	900	200	1200	110
500	560	590	12	32x12	300	150	1000	220	1300	123
560	625	660	12	32x14	340	170	1120	235	1400	228
630	695	730	12	32x14	380	190	1260	250	1500	310
710	775	810	12	48x14	430	210	1420	265	1650	380
800	865	900	12	48x14	480	240	1600	280	1760	445
900	965	1000	12	64x14	540	270	1800	295	1900	560
1000	1065	1100	12	64x14	600	300	2000	310	2000	620
1120	1205	1250	12	64x14	670	340	2240	330	2100	760
1250	1335	1380	12	64x14	750	380	2500	350	2200	990

