

**DESCRIPTION**

Ventilation hoods FH type are destined for installation in ventilation systems of seagoing ships as well as offshore objects. They are not provided with closing device, relevant SOLAS regulation must be observed. FH type hoods are designed for installation on the open decks. Coaming is made of carbon steel St3Sx, painted with set of marine paints, wire gauze is made of stainless steel 316 and shaft bearings are made of stainless steel. By ordering specify required nominal diameter DN.

TECHNICAL SPECIFICATION & DIMENSIONS

DN	Dimensions [mm]											Weight [kg]
	ØA	ØB	C	NxØD	E	ØG	J	K	L	M	Md	
200	260	290	10	16x12	170	400	300	130	160	4	M8	46
250	310	340	10	16x12	215	500	380	165	160	4	M10	72
315	370	405	12	24x12	270	630	480	210	200	4	M10	80
400	460	490	12	24x12	340	800	610	265	260	4	M10	99
500	560	590	12	32x12	425	900	765	330	320	5	M12	163
560	625	660	12	32x14	480	1000	855	370	360	5	M12	207
630	695	730	12	32x14	540	1150	960	420	400	5	M16	277
710	775	810	12	48x14	600	1300	1080	470	450	5	M16	337
800	865	900	12	48x14	680	1500	1220	530	500	5	M16	396
900	965	1000	12	64x14	760	1600	1380	600	560	5	M20	365
1000	1065	1100	12	64x14	850	1800	1530	665	630	5	M20	544
1120	1205	1250	12	64x14	950	2000	1700	740	700	5	M20	684
1250	1335	1380	12	64x14	1060	2300	1900	830	800	5	M20	940
1400	1485	1530	12	64x14	1180	2600	2150	930	900	5	M20	1250
1600	1685	1730	12	64x14	1320	3000	2450	1050	1000	5	M20	1570

